

# Product Bulletin

## Coatings

NextGen Epoxy™  
Waterborne System for  
Ultra-Low VOC Coatings

**EPI-REZ™ Resin 7520-WD-52 and  
EPIKURE™ Curing Agent 8530-W-75**



### Our Products for Americas



**EPI-REZ Resin 7520-WD-52 is a low VOC, solid epoxy resin dispersion that provides a range of properties comparable to traditional solvent-borne systems. EPIKURE Curing Agent 8530-W-75 is a solvent-free curing agent supplied as a water-reducible aqueous solution. The combination of these two products forms the NextGen Epoxy waterborne system, designed for use in concrete floor coatings or as a protective coating for metal substrates. This system provides an applied cost that is more cost-competitive than that of traditional waterborne epoxy systems.**

### Features

- Ultra-low VOC (<50 g/L for concrete and <100 g/L for metal)
- Extended pot life (5 hours with good gloss)
- High gloss, fast dry and cure times
- Superior corrosion resistance (1000 hours salt spray at 3-4 mils DFT)
- Low amine hydrogen equivalent weight (AHEW)
- Improved balance of cost & performance
- Superior freeze/thaw stability (Passes 3+ Cycles; -5 °C to 23 °C)

### Physical Properties

Product	% Wt. Solids	Viscosity, cP	Solvent Content, % wt	Equivalent Weight, g/eq
EPI-REZ 7520-WD-52	51 – 53	1,000 – 6,000	5	475 – 575 (BoS)
EPIKURE Curing Agent 8530-W-75	73 – 77	6,000 – 13,000	0	120 (as supplied)

### Formulation and Performance

EPIKURE Curing Agent 8530-W-75 can be diluted up to 50% by weight with water to form a clear to hazy solution. Amount of dilution and resultant component stability should be validated by the formulator.

The NextGen Epoxy waterborne system (EPI-REZ Resin 7520-WD-52 and EPIKURE Curing Agent 8530-W-75) can be formulated to meet stringent VOC regulations in concrete or metal coatings. This system offers a more cost competitive, waterborne alternative to traditional solvent-based, two-component epoxy systems with equivalent performance.

### Applications

- Railway Coatings
- Concrete Coatings for floors, walls and garages
- Industrial Maintenance Coatings for metal
- Automotive Parts and Accessories

# Hexion: Helping you make it in today's world.

Our global team produces the best in specialty chemicals and performance materials and provides the technical expertise to customize them to your exact needs. The result? Specific solutions, not generic products, leading to thousands of breakthroughs that improve bottom lines and enhance lives.

## Reach our Global Customer Service network at:

### U.S., Canada and Latin America

+1 888 443 9466 / +1 614 986 2497

E-mail: [4information@hexion.com](mailto:4information@hexion.com)

### Europe, Middle East, Africa and India

+800 836 43581 / +40 212 534 754

E-mail: [4information.eu@hexion.com](mailto:4information.eu@hexion.com)

### China and Other Asia Pacific Countries

+86 2 1386 04835

E-mail: [4information.ap@hexion.com](mailto:4information.ap@hexion.com)

Please refer to the literature code HXN-730 when contacting us.



## World Headquarters

180 East Broad Street  
Columbus, OH 43215-3799

© 2016 Hexion Inc. All rights reserved.

® and ™ denote trademarks owned or licensed by Hexion Inc.

HXN-730 US 02/17

The information provided herein was believed by Hexion Inc. ("Hexion") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use. All products supplied by Hexion are subject to Hexion's terms and conditions of sale. HEXION MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY HEXION, except that the product shall conform to Hexion's specifications. Nothing contained herein constitutes an offer for the sale of any product.